

CLAMPING SLEEVES BARFEED COLLET (FINGER CHUCK) AS IEMCA

中意送料夹



Mode	D	Thread G	Length L	Clamping diameter S min.-max.	NO.
4#-5	5	M4*0.7	98	0.8-4	1
5#	5	M4*0.5	37	2-4	2
4#-7	7	M4*0.7	98	0.8-6	3
7.5#	7.5	M5*0.8	40	2-6	4
10#	10	M6*0.75	42	1.5-8.5	5
12#	12	M7*0.75	42	1.5-10.5	6
15#	15	M8*1.0	42	2-13	7
16#	16	M8*1.0	42	12-14	8
20#	20	M10*1.0	60	3-18	9



Mode	D	Thread G	Length L	Clamping diameter S min.-max.	NO.
23#	23	M10*1.0	60	16-21	1
25#	25	M10*1.0	60	16.5-22	2
27#	27	M10*1.0	60	16.5-23	3
32#	32	M25*1.5	80	4-30	4
35#	35	M25*1.5	80	28.5-32	5
37#	37	M25*1.5	80	31-34	6
38#	38	M25*1.5	80	31-35	7
40#	40	M25*1.5	80	21-36.5	8



Mode	D	Thread G	Length L	Clamping diameter S min.-max.	NO.
42#	42	M25*1.5	80	31.5-40	1
45#	45	M25*1.5	80	38.5-42.2	2
51#	51	M25*1.5	80	42.5-48	3

REVOLVING TIP (ROTATING) AS IEMCA

中意IEMCA中轴



Mode	D	Length L	Finger chuck regulatory teeth	Plusher regulatory teeth	NO.
7.5#	7.5	151	M5P0.5		1
10#	10	167	M6P0.75	PIN=3.0	2
12#	12.5	173	M7P0.75	PIN=3.0	3
15#	15.5	195	M8P1.0	PIN=4.0	4
16#	16.5	195	M8P1.0	PIN=4.0	4
18#	18.5	195	M8P1.0	PIN=4.0	4
19#	19.5	195	M8P1.0	PIN=4.0	4
20#	20.5	207.5	M10P1.0	PIN=4.0	5
22#	22.5	207.5	M10P1.0	PIN=4.0	6
23#	23.5	207.5	M10P1.0	PIN=4.0	6
25#	25.5	207.5	M10P1.0	PIN=5.0	7
27#	27.5	207.5	M10P1.0	PIN=5.0	7



Mode	D	Length L	Finger chuck regulatory teeth	Plusher regulatory teeth	NO.
30#	30.5	165	M25P1.5	PIN=5.0	1
32#	32.5	165	M25P1.5	PIN=5.0	1
35#	35.5	165	M25P1.5	PIN=5.0	2
37#	37.5	165	M25P1.5	PIN=5.0	2
38#	38.5	165	M25P1.5	PIN=5.0	2
40#	40.5	165	M25P1.5	PIN=6.0	3
42#	42.5	165	M25P1.5	PIN=6.0	3
45#	45.5	165	M25P1.5	PIN=6.0	3
51#	51.5	165	M25P1.5	PIN=6.0	4

CLAMPING SLEEVES BARFEED COLLET (FINGER CHUCK) AS LNS(FEDEK)

LNS(FEDEK)冠通艾恩司送料夹



Mode	D	Thread G	Length L	Clamping diameter S min.-max.	NO.
8.5#-9.5	9.5	M5*0.8	45	1.5-7.8	1
8.5#-10	10	M5*0.8	45	7.9-8.5	1
8.5#-12	12	M5*0.8	45	3.0-10.5	1
8.5#-13	13	M5*0.8	45	10.8-11	1
8.5#-14	14	M5*0.8	45	11.5-12	1
8.5#-15	15	M5*0.8	45	12.5-13	1
8.5#-16	16	M5*0.8	45	13.5	1

Mode	D	Thread G	Length L	Clamping diameter S min.–max.	NO.
20#-15	15	M9*1.0	60	2.5-13	2
20#-18	18	M9*1.0	60	11.5-15.1	2
20#-19	19	M9*1.0	60	15.2-16	2
20#-20	20	M9*1.0	60	16.5-18	2
20#-22	22	M9*1.0	60	18.5-19	2
20#-24	24	M9*1.0	60	19.5-21	2
20#-25	25	M9*1.0	60	21.5-22	2
xt326-22	22	M9*1.0	60	18-19.5	3
xt326-23	23	M9*1.0	60	20-21	3
xt326-26	26	M9*1.0	60	21.5-23	3
xt326-28	28	M9*1.0	60	24-26	3



Mode	D	Thread G	Length L	Clamping diameter S min.–max.	NO.
SN20	20	M10*1.0	60	3.0-18.0	1
SN25	25	M10*1.0	60	16.5-23	1
SN27	27	M10*1.0	60	16.5-25	1
SN32	32	M17*1.0	70	23.5-28	2
SN35	35	M25*1.0	80	28.5-33	3
37#	37	M25*1.0	80	31-34	4
38#	38	M25*1.0	80	31-35	4
42#	42	M25*1.0	80	31.5-40	4
45#	45	M25*1.0	80	38.5-42.2	5
51#	51	M25*1.0	80	42.5-48	6

LNS(FEDEK)REVOLVING TIP (ROTATING)

LNS(FEDEK)冠通艾恩司中轴



Mode	D	Length L	Finger chuck regulatory teeth	Plusher regulatory teeth	NO.
7#	8	61.1	M4P0.7	M6P0.75	1
8.5#	9.5	63.5/66.3	M5P0.8	M7P0.75	2
8.5#	10	59.5/66	M5P0.8	M7P0.75	3
8.5#	10	61.1	M5P0.8	M7P0.75	
8.5#	10	64.5	M5P0.8	M7P0.75	4
12#	12	64.5	M5P0.8	M7P0.75	5
20#	15	92.2	M9P1.0	M12P1.0	6
20#	15	92.2	M9P1.0	M12P1.25	7
SN20	20.5	207.5	M10P1.0	PIN=4.0	8
SN22	22.5	207.5	M10P1.0	PIN=4.0	8
SN23	23.5	207.5	M10P1.0	PIN=4.0	8
SN25	25.5	207.5	M10P1.0	PIN=5.0	9
SN27	27.5	207.5	M10P1.0	PIN=5.0	10
SN32	32.5	165	M25P1.5	PIN=5.0	11



Mode	D	Length L	Finger chuck regulatory teeth	Plusher regulatory teeth	NO.
SN32	32.5	165	M25P1.5	M27	1
SN35	35.5	165	M25P1.5	PIN=6.0	2
SN35	35.5	165	M25P1.5	M29	3
SN37	37.5	165	M25P1.5	PIN=6.0	4
SN38	38.5	165	M25P1.5	PIN=6.0	5
SN42	42.5	165	M25P1.5	PIN=6.0	6
SN42	42.5	165	M25P1.5	M34	7
SN45	45.5	165	M25P1.5	PIN=6.0	8
SN45	45.5	165	M25P1.5	M38	9
SN51	51.5	165	M25P1.5	PIN=6.0	10
SN51	51.5	165	M25P1.5	M42	11